

Two Hole Terminal Lug

DAR's Two-Hole Heavy Duty Lugs are the perfect solution for applications requiring two bolts to prevent rotation or movement of the lugs. These lugs are designed for heavy-duty industrial use, where mechanical strength is essential. They are made from tin-plated copper to improve electrical conductivity and prevent oxidation. The flat contact surface and precise stud holes are designed to meet metric standards, while the chamfered mouth allows for easy cable insertion. DAR's Two-Hole Heavy Duty Lugs are available with or without an inspection window.

Conductor Size	E	A	C	D	G	H	B	J
25	13	6.8	10	14	15	17	37	123
35	13	8.2	12.5	19.5	15	17	37	124
50	13	9.5	14.5	20	14	16	39.5	124
70	13	11	16	23	14	16	42	126
95	14.5	13.5	19	27	16	18	52	144.5
120	14.5	15	20.5	29	16	18	56.5	144.5
150	17	16.5	23	32	14	16	56.5	144.5
185	17	18.5	24	32.7	16	18	65	156
240	17	21	26	36	16	20	65	160
300	17	23.5	32	45	17	19	79.5	175
400	16.5	27	38	53	17	19	81	182.5
500	21	30.3	41	57	20	20	85.5	194.5
630	21	33.4	43	61	20	20	95.5	206.5



DAR
FOR ENGINEERING SUPPLIES